

# AVM457A 2 Megapixel IR Network Camera



# ETS

### **FEATURES**

- Easy network setup with your iPhone / iPad
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- ONVIF standard supported to simplify system integration
- External alarm I/O device connection
- IR LED built-in for **night surveillance** with effective range up to 20 meters
- Remote Surveillance
  - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
  - -- Free PC program, CMS Lite, for 32CH devices monitoring on Windows operating system
  - -- Push Video available on your iOS and Android devices when used with Push Video NVR series.

### **SPECIFICATIONS**

■ Network	
Network Compression	H.264 / MPEG4 / MJPEG
Multiple Video Streaming (Encode Modes, IPS, Resolution)	YES
LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP,IPv4, Bonjour, UPnP, DNS,UDP,IGMP, QoS
ONVIF Compatible	YES (Profile S)
Frame Rate	30fps
Number of Online Users	10
Security	(1) Multiple user access levels with password (2) IP address filtering
	(3) Digest authentication
Remote Access	(1) Internet Explorer on Windows operating system     (2) CMS Lite, 32CH CMS software for Windows operating system     (3) EagleEyes on iOS & Android mobile devices
■ Camera	
Image Sensor	1/2.9" SONY CMOS image sensor
Video Resolution	1920 x 1080 / 1280 x 720 / 640 x 480 / 320 x 240
Min Illumination	0.1 Lux / F1.5, 0 Lux (LED ON)
Shutter Speed	1/2 to 1/10,000 sec
S/N Ratio	More than 48dB (AGC off)



## **SPECIFICATIONS (Continued)**

■ Camera		
Lens	f3.8mm / F1.5	
Viewing Angle	73.2°(Horizontal) / 47.4°(Vertical) / 85.4°(Diagonal)	
IR LED	35 Uints	
IR Effective Range	Up to 20 meters	
IR Shift	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
POE	YES (IEEE 802.3af)	
External Alarm I/O	YES	
RAM	20MB	
IP Rating	IP67	
Power Source (±10%)	12V / 1A	
Operating Temperature	-25℃~50℃	
Operating Humidity	90% or less relative humidity	
Power Consumption (±10%)	7.1W (PoE); 7.1W (PoN) ; 6W (DC Adapter)	
Net Weight (Kg)	0.75	
■ Others		
Mobile Surveillance	iPad / iPhone / Android mobile device	
Motion Detection	YES	
Event Notification	FTP / Email / SMS	
RTC (real-time clock)	YES	
Digital Pan / Tilt / Zoom	YES	
Minimum Web Browsing Requirements	<ul> <li>Intel core i3 or higher, or equivalent AMD</li> <li>2GB RAM</li> <li>AGP graphics card, Direct Draw, 32MB RAM</li> <li>Windows 10, Windows 8, Windows 7, Windows Vista &amp; Windows XP, DirectX 9.0 or later</li> <li>Internet Explorer 7.x or later (Windows Edge not supported)</li> </ul>	

<sup>\*</sup>The specifications are subject to change without notice

### **DIMENSIONS** Dimensional tolerance: ± 5mm





